



14700 Downey Avenue
P.O. Box 1418
Paramount, CA 90723-1418
(562) 531-2060

PRODUCT SPECIFICATIONS

PRODUCT: High Performance Seal

GRADE:

PRODUCT CODE: 13828

DESCRIPTION: A hot-applied, quick-setting asphalt sealer for filling cracks and pavement surface imperfections, resulting in a wearing course that is immediately available for traffic. Also excellent as a hot-applied no-track tack coat.

MEETS SPECIFICATIONS: Paramount Petroleum Corp.

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS*
Original Asphalt:				
Rotational Viscosity, 275°F, cP	D4402	T316	3500 max	2200
Penetration, 77°F, 100g, 5s	D5	T49	5-40	8
Flash Point, C.O.C., °F	D92	T48	450 min	600
Softening Point °C	D36	T53	165 min.	175
Solubility in TCE, wt %	D2042	T44	98 min	99+
Specific Gravity, 77/77°F	D70	T228		1.018
Specific Gravity, 60/60°F	D70	T228		1.024
API Gravity, 60°F	D70	T228		6.7
Density, 60F, Lbs/Gallon	D70	T228		8.53
Dynamic Shear @ 82°C, kPa		TP5	1.0 min	5.1
Percent Polymer Content	Cal 401		2-5	3

*Values shown as typicals may, at times, be superseded by results, which are current at a particular time.

AVAILABILITY: Special Order

DOT SHIPPING NAME: UN3257, Elevated temperature liquid, n.o.s., 9, III

RELEASED: 09/01/04