



14700 Downey Avenue
P.O. Box 1418
Paramount, CA 90723-1418
(562) 531-2060

PRODUCT SPECIFICATIONS

PRODUCT: SATURANT

GRADE: 701 **PRODUCT CODE:** 12101

DESCRIPTION: A vacuum steam refined straight run asphalt for use as a felt saturant.

MEETS SPECIFICATIONS: Paramount Petroleum

TESTS	ASTM METHOD	AASHTO METHOD	SUMMER SPECS.	WINTER SPECS.	TYPICAL ANALYSIS ¹
Penetration, 77°F, 100g, 5s	D5	T49	80-95	85-100	92
Abs. Viscosity, 140°F, Poise	D2171	T202			1071
Flash Point, C.O.C., °F	D92	T48	500 min	500 min	575
API Gravity, 60°F	D70	T228			6.7
Density, 60°F, lbs/gallon	D70	T228			8.53
Softening Point, °F	D36	T53	110 min	110 min	113

¹Values shown as typicals may, at times, be superseded by results which are current at a particular time.

AVAILABILITY: Readily available

DOT SHIPPING NAME: UN3257, Elevated temperature liquid, n.o.s., 9, III

DOT PLACARD: Hot, 3257

RELEASED: 11-01-2007