



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

## PRODUCT SPECIFICATIONS

**PRODUCT:** BUILT-UP ROOFING ASPHALT

**GRADE:** TYPE III

**PRODUCT CODE:** 12745

**DESCRIPTION:** An uncatalyzed air blown asphalt coating used in the manufacture of roofing products, or used for mopping on roofs with severe slopes or in warmer climates.

**MEETS SPECIFICATIONS:** ASTM D312

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS <sup>1</sup>
Softening Point, °F	D36	T53	185-205	202
Flash Point, COC, °F	D92	T48	520 min	540
Penetration, 32°F, 200g, 60s	D5	T49	6 min	13
Penetration, 77°F, 100g, 5s	D5	T49	15-35	20
Penetration, 115°F, 50g, 5s	D5	T49	90 max	35
Ductility 77°F, 5cm/min, cm	D113	T51	2.5 min	2.5
Solubility in TCE, wt. %	D2042	T44	99.0 min	99.9
API Gravity, 60°F	D70	T228		6.8
Density, 60°F, Lbs/Gallon	D70	T228		8.52

<sup>1</sup>Values shown as typicals may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Readily available

**DOT SHIPPING NAME:** UN3257, Elevated temperature, liquid, n.o.s, 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 10-01-2007